


# 1. PRIMER / ADHESIVE

# DANOSA PRIMER COMMERCIAL PRODUCT DATA SHEET



## DESCRIPTION

Danosa Primer is designed to be used as a first waterproofing layer over concrete, wood, etc. It increases adhesion and compatibility of Danosa's Roof Systems over these surfaces. It meets ASTM D-41 specification.

## APPLICATION

Danosa Primer can be applied with a roller, brush or spraying equipment.

## SURFACE PREPARATION

All surfaces should be free from oil, grease, dirt and loose materials.

## COVERAGE RATE

Apply a uniform layer of the material at a rate of one gallon per 100-150 square feet. Allow it to dry for 24 hours or less before installing the roof system.

## CLEANING

Can use Varsol or Kerosene to thin the material (if needed) and clean the equipment.

## PACKAGING

Available in 5-gallon pails.

## WARNING

This product is flammable. Keep away from heat sources, sparks, and flames. Must be applied with adequate ventilation.

## OVEREXPOSURE EFFECTS

High vapor concentrations could cause eye and respiratory tract irritation, headaches, and dizziness. Repeated contact with skin could cause irritation and dermatitis.

## FIRST AID AND EMERGENCY PROCEDURE

Eye contact: Wash with clean water. If irritation persists, contact a doctor,

Skin contact: discard any contaminated cloths. Clean with vegetable oil mineral oil, and then wash with soap and water.

Inhalation or ingestion: See a doctor.



## PROTECTION INFORMATION

Use solvent resistant gloves and safety glasses when handling this product. Use adequate ventilation.



Please contact the Danosa Sales office for specific information as required.

Rev 10/2020

**danosa • danosa • danosa • danosa • danosa • danosa • danosa • danosa • danosa**

Lot. 29, Luchetti Industrial Complex, Bayamón, Puerto Rico 00961 • PO Box 13575 Santurce Station, San Juan, PR 00908

Tel. (787) 785-4545 • Fax. (787) 787-3902

Website: [www.danosapr.com](http://www.danosapr.com)

Email: [sales@danosapr.com](mailto:sales@danosapr.com)